DELHI URBAN SHELTER IMPROVEMENT BOARD GOVERNMENT OF N.C.T. OF DELHI OFFICE OF THE EXECUTIVE ENGINEEER, C-1, Raja Garden, Near DTC Bus Terminal, New Delhi-110027

NIQ No.11/EEC-1/DUSIB/2018-19/D-&1)

Dated: 23 01 19

NOTICE INVITING QUOTATION

Executive Engineer, C-1, DUSIB on behalf of Delhi Urban Shelter Improvement Board invites quotations from intending agencies on percentage rates basis in sealed cover for the following works:-

| SL. NO | Name of work | Estimated Cost | Time of Completion | |
|--------|---|----------------|-----------------------|--|
| 1. | N.O.W: JSC(Revenue) SH: Repair of portion of settled flooring of WCs, Baths, Passages, Lobby of JSC at JJC Shamshan Bhoomi, Hastsal (AC-31) | Rs. 91608.00 | 15 days | |

The quotations shall reach the office of the Executive Engineer,C-1, DUSIB, Raja Garden, New Delhi-110027 latest by 3.00 PM on 25.01.2019 which shall be opened on 25.01.2019 at 3.30 PM in the presence of intending quotationers or their representatives. The intending quotationers may collect the schedule of quantities on DUSIB website and other information from the office of the Executive Engineer,C-1, DUSIB. The terms & Conditions of the quotation are as follows:-

- 1. The work shall be carried out as per CPWD specifications.
- 2. Payment shall be made as per actual measurement at site of work.
- 3. No T&P shall be issued.
- 4. Conditional quotations shall be liable to rejection.
- 5. For any disputes the matter shall be referred to SE-I DUSIB for final decision and the same shall be binding upon both the parties.
- 6. Statutory recoveries shall be deducted from the bills of contractor as per rules.
- 7. Work shall be completed to the satisfaction of Engineer-in-charge.
- 8. Debarred/blacklisted agencies shall not be permitted to submit quotations.

EXECUTIVE ENGINEER, C-1

NOTICE BOARD

Publication on DUSIB Website

DELHI URBAN SHELTER IMPROVEMENT BOARD OFFICE OF THE EXECUTIVE ENGINEER C-1

NAME OF WORK :-Pay &Use JSC Sub head: Repair of portion of settled flooring of WCs, Baths, Passages, Lobby of JSC at JJ Cluster Shamshan Bhoomi, Hastsaal(AC-31)

| No. | DSR | DESCRIPTION | Schedule Otv | | P . | P. C. | |
|-----|----------------|---|-----------------|----------|--------------------|--------------------------------|---------------|
| | Item | | Qty | Unit | Rate Rs. | Rate in Words | Amount (in |
| | No / | <u>, </u> | ' | | | 1 | Rs.) |
| | Page | · 1 | ·] | (| | | 1 |
| _ | No 4 1 2 D | Deputied | ·] | (% | | | |
| 1 4 | 4.1.3 P | Providing and laying in position cement concrete of | 0.21 | cum | 5/191 0= | Rs Five Thousand | 1151 21 |
| | 65 | specified grade excluding the cost of centering and | 1/ | -with | | Four Hundred | 1151.21 |
| | - 1 | Shuttering - All work up to plinth level . 1.2.4 /1 | 100 | (1 | | EightyOne Paise | (|
| | | cement : 2 coarse sand(zone-III) : 4 graded stone | 1 | 1 | 1 | NinetyFive Only | Ţ |
| | - 1 | aggregate 20 mm nominal size) | 1 | 1 | | 1 | 1 |
| _ | | | | <u> </u> | | <u> </u> | |
| 2 4 | 4.1.10 P 05 | Providing and laying in position cement concrete of | 3.82 | cum | | Rs Four Thousand | 16078.57 |
| | P-85 | specified grade excluding the cost of centering and | V | 1 | 1/ | Two Hundred Nine Paise Five | |
| | | shuttering - All work up to plinth level : 1:5:10 (1 | | 1 | | Nine Paise Five Only | |
| | - 1 | cement : 5 coarse sand(zone-III) : 10 graded stone | 1 | 1 | | | , |
| | 1 | aggregate 40 mm nominal size) | · 1 | 1 | 1 | 1 | |
| 3 | 6.1.1 | Brick work with common burnt clay F.P.S. (non | 0.35 | - | 4070.5 | Rs Four Thousand | 12/2 50 |
| ٦ | | modular) bricks of class designation 7.5 in | 0.25 | cum | 4370.30 | Nine Hundred | 1242.58 |
| | | foundation and plinth in: Cement mortar 1:4 (1 | V | ' | | Seventy Paise | |
| | | cement : 4 coarse sand) | · | ' | 1 | Thirty Only | |
| 4 : | $\overline{}$ | Kota stone slab flooring over 20 mm (average) thick | 14.90 | sqm | 1158.10 | Rs One Thousand | 17255.69 |
| | | base laid over and jointed with grey cement slurry | / / | '"" | - Iso.10 | One Hundred | 17255.05 |
| | 100 | mixed with pigment to match the shade of the slab | | ' | 1 | FiftyEight Paise Ten Only | |
| , | | including rubbing and polishing complete with base | | 1 | 1 | Ten Only | 1 |
| | | of cement mortar 1 : 4 (1 cement : 4 coarse sand) : | ' | 1 | 1 | T. | 4 |
| | - 1 | 25 mm thick. | ' | 1 | 1 | | |
| | | West at the state of the state | 11.5 | igsquare | | Do C | 10000 |
| 5 | | Kota stone slab flooring over 20 mm (average) thick | | () | 743.1 0 | Rs Seven Hundred | |
| | | base laid over and jointed with grey cement slurry | | () | 776.90 | Ten Only | 11.2 17.4 |
| | | mixed with pigment to match the shade of the slab | | 1 | 176.10 | ni hear al | ٧ |
| 14 | | including rubbing and polishing complete with base of cement mortar 1: 4 (1 cement: 4 coarse sand): | 1 | () | 1 | | |
| | | of cement mortar 1 : 4 (1 cement : 4 coarse sand) : 25 mm thick. Old Kota stone to be used is | ' | 1 | Ţ | | |
| | - 1 | 25 mm thick. Old Kota stone to be used is available at site | ' ' | () | 1 | | |
| | 1 | Cranable at site | ' | 1 | 1 | | |
| 6 | 11.27 | Kota stone slabs 20 mm thick in risers of steps, | 2.14 | sgm | 1220 20 | 0 Rs One Thousand | 4 2640 75 |
| | | skirting, dado and pillars laid on 12 mm (average) | 24 2 1 | Squi | 1238.21 | Two Hundred | nd 2649.75 |
| | | thick cement mortar 1:3 (1 cement 3 coarse sand) | | | | ThirtyEight Paise | e |
| | - 1 | and jointed with grey cement slurry mixed with | | | | Twenty Only | * F |
| | | pigment to match the shade of the slabs, including | | | | 1 | |
| | | rubbing and polishing complete. | ' | | | 1 | |
| | | Samplete. | ' ' | | | 1 | |
| 7 | Appd I | Kota stone slabs 20 mm thick in risers of steps, | 2.14 | + | 010- | 5 Rs Fight Harri | vd 4254.55 |
| - 1 | | skirting, dado and pillars laid on 12 mm (average) | | 1 | | 75 Rs Eight Hundre | W |
| | | thick cement mortar 1:3 (1 cement 3 coarse sand) | | | 0.5 (10) | SeventyFive On | |
| | | and jointed with grey cement slurry mixed with | | | | , | |
| 1 | | | | | 0.9 | 1 | |
| | | pigment to match the shade of the slabs, including | | | 102 | | |
| 1 | | rubbing and polishing complete .Old Kota stone to | 1 | | | 1 | To the second |
| 1 | L | be used is available at site | 1 | | | 21.4 | |
| L | | | 1 | | L | | |

| | 11.30 | Providing and fixing ist quality ceramic glazed wall | 1.00 T | - | | | |
|-----|---------|--|--------|-------|----------|--------------------------------------|------------|
| • | | tiles conforming to IS: 15622 (thickness to be | 1.00 | sqm | 744.80 R | s Seven Hundred 74 | 4.80 |
| | | specified by the manufacturer), of approved make, in all colours, shades except by | | | 1 | ourtyFour Palse lighty Only | 72 |
| | | in all colours, shades except burgundy, bottle | | | l' | Burth Outh | |
| | 1 | green, black of any size as approved by Engineer-in- | | - 1 | - 1 | | 1 |
| | 1 | | | - 1 | | | l |
| | 1 | | | | - 1 | | 1 |
| | | | | | - 1 | | 1 |
| | | The sum including poleties in | | | 1 | | |
| | | with pigment of matching shade | | | | | 1 |
| | 1 | complete | | | 1 | | 1 |
| | | | | | 1 | | |
| 9 | 11 20 | Devid II | | | | | 1 |
| 9 | 11.39 | Providing and laying Ceramic glazed floor tiles of | 8.40 | sqm | 699.35 | to Six Hundred 5 | 782-14 |
| | | size 300x300 mm(thickness to be specified by the | 1.0 | 34111 | 8 22.45 | | 900.58 |
| | | indidideturer) of 1st quality conforming to it | | | 8 22.45 | DistyFive Only | ,,,,, |
| | | 13022 of approved make in colours such as White | | | | forty fire | 1 |
| | | livory, Grey, rume Red Brown, laid on 20 mm thick | | | | | |
| | | cement mortar 1:4 (1 Cement :4 Coarse sand) | | | l | | |
| | | Jointing with grey cement slurry @ 3.3kg/sgm | | | - 1 | 1 | |
| | | including pointing the joints with white cement and | | | | 1 | |
| | | matching pigment etc.,., complete. | | | | | |
| 10 | 12.2.2 | 15 | | | | | |
| 10 | 13.2.2 | 15 mm cement plaster on rough side of single or | 2.00 | sqm | 185.20 | | 370.40 |
| | /P-222 | half brick wall of mix: 1:6 (1 cement : 6 fine sand) | 1 | | 120 | EightyFive Paise Twenty Only | 6 |
| | | | | | | wenty only | |
| 11 | 15 2 1 | Domelishing course | | | | | |
| 11 | 15.2.1 | Demolishing cement concrete manually / by | 3.82 | cum | 997.05 | Rs Nine Hundred NinetySeven Paise | 3808.73 |
| | | mechanical means and disposal of material within | 10.0 | | į. | Five Only | (|
| | | 50 metres lead as per direction of Engineer - in - | 9 | - 1 | | | |
| | | Charge: Nominal concrete 1:3:6 or richer mix (i/c | | - 1 | | | |
| 12 | 15 2 2 | equivalent design mix) Demolishing cement concrete manually / by | 2.02 | | 615.45 | Rs Six Hundred | 2240.07 |
| 12 | 15.2.2 | mechanical means and disposal of material within | 3.82 | cum | 615.15 | Fifteen Paise | 2349.87 |
| | | 50 metres lead as per direction of Engineer - in - | - 1 | - 1 | A | Fifteen Only | 3" |
| | | Charge: Nominal concrete 1:4:8 or leaner mix (i/c | | | | | |
| | | equivalent design mix) | | - 1 | | | |
| | | equivalent design mix/ | | | | | |
| 13 | 15.7.4 | Demolishing brick work manually / by mechanical | 0.20 | cum | 842 75 | Rs Eight Hundred | 168.55 |
| | | means including stacking of serviceable material | الا | | 042.73 | FourtyTwo Paise | 108.55 |
| | | and disposal of unserviceable material within 50 | | - 1 | L | SeventyFive Only | |
| - 1 | | metres lead as per direction of Engineer - in - | | | | | |
| | | Charge : In cement mortar | | | | | |
| | | S. S. Be . III cellient liloitui | | | | 1 | |
| 14 | 15.56 | Dismantling old plaster or skirting raking out joints | 10.00 | sqm | 22.4/ | Rs TwentyTwo | 224.00 |
| - ' | 25.50 | and cleaning the surface for plaster including | 10.00 | 34III | 22.40 | Paise Fourty Only | 224.00 |
| | | disposal of rubbish to the dumping ground within | | | | | , F |
| | | 50 metres lead | | | | | 1 |
| 15 | 15.60 | Disposal of building rubbish / malba / similar | 0.70 | | 455 | | |
| 13 | | | 9.79 | cum | 120.5 | Rs One Hundred | 1180.18 |
| | | unserviceable, dismantled or waste materials by | ~ | ĺ | V | Twenty Paise FiftyFive Only | L |
| | | mechanical means, including loading, transporting, | | | | l,e only | |
| | | unloading to approved municipal dumping ground | | | | , | 1 |
| | | or as approved by Engineer-in-charge, beyond 50 m | | | | 1 | 1 |
| | Į. | initial 'lead, for all leads including all lifts involved. | | | | 1 | |
| | | | | | | | |
| 16 | Į. | Providing and fixing white vitreous china water | 7.00 | No. | 1456.6 | O Rs One Thousan | d 10196.20 |
| | l | closet squatting pan (Indian type) : | ν | 1 | V | Four Hundred | |
| | - 1 | *** | | | | FiftySix Paise Six | rty |
| | | 1 | | ı | 1 | Only | 1 |
| | | | | | | 10 | 571.07 |
| 1 | 7.13. (| Orissa pattern W.C. pan of size 580x440 mm | | | | | |

| | F | Providing and fixing soil, waste and vent pipes : | 6.30 V | | 862.80 • | Rs Eight Hundred SixtyTwo Paise Eighty Only | 5435.64 |
|------|-----------|--|------------|------|-------------|--|-----------------------|
| - | \neg | 100 mm dia. | | | | | |
| 17 | .35. | Sand cast iron S&S pipe as per IS: 1729. | | | | | |
| 1 | 1.1 | | | | | | |
| 1. | 7.39. | Providing and fixing plain bend of required degree 100 mm Sand cast iron S & S as per IS: 1729 | 1.00 | each | 433.70 V | Rs Four Hundred ThirtyThree Paise Seventy Only | 433.70 |
| | | D. Providing and fixing sand cast iron trap of self | 2.00 | each | 848.60 | Rs Eight Hundred FourtyEight Paise Sixty Only | 1697.20 |
| | | or hinged gratting with or with out vent arm complete including cost of cutting and making good the wall & floors - : 100mm inlet and 100 mm outlet : Sand cast iron S&S as per IS: 1729 | | | | | |
| 20 1 | 15 | 5.25 Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 | 40.90 V | Sqm | 109.35 | Rs One Hundred Nine Paise ThirtyFive Only | 4472.42 |
| | 1 | metres lead | | | | 89777.86 | 83595.6 7 |
| | + | 7. | | | | | |
| _ | + | | | | | 11446.68 | 10658.45 |
| | \top | Add 12.75% due to Cost Index | | | | 101224.54 | 94254.12 |
| | \forall | 12000 | | | | - 9616.33 | -1 358.95 |
| | | Deduct 9.75% as per order of GNCTD | | | | ÷ | 0200E 17 |
| | | | | | | 91608.21 | 9 2895.1 7 |
| 1 | _ | | | | | 916.08 | 9. |
| 1 | | ADD IV. Contugenen | | - | | | 1857.90 |
| + | | Add 12% Contingencies & Labour Cess | | - | | 93440.3> | |
| + | | | | | | | 94 753 .07 |
| H | | | | | | Say 4 3400.0 | 94 800: 00 |